


NCA-WLAN-EU Wireless installation dongle EU



The wireless installation dongle connects to the USB-C port on the camera to provide efficient wireless commissioning for Bosch cameras. It enables easy installation and fast configuration of Bosch cameras in combination with the Project Assistant app. Initial camera configuration, including pre-commissioning, setup of field of view, and image settings can be done faster. It also offers access to the full camera firmware GUI. The advanced project assistant mode allows applying pre-setup configurations for even faster camera deployment as well as the option to generate full project reports.

The wireless installation dongle is supported by cameras with USB-C port and with firmware 8.80 or later and with any mobile device (iOS, Android, Windows) with the Bosch Project Assistant app.

Regulatory information

Standard	Type
Emissions	EN 301 489-17 EN 301 489-1 EN 300 328 EN 61000-3-2:2019/A1:2021 EN 61000-3-3:2013/A2:2021/AC:2022-01 FCC Title 47 Part 15C with ID (Bluetooth/WiFi) (Part 15.247 and 15.207 & 15.209)
Environmental	RoHS (2015/863/EU): EN 50581:2012



- ▶ Compact 802.11b/g/n wireless installation dongle
- ▶ Automatic detection in Bosch Project Assistant
- ▶ Transmission data rate up to 150 Mbps
- ▶ Approved for Bosch surveillance cameras

Standard	Type
	EMC EU: EN 55024:2010/A1:2015; EN 55032:2015 EMC USA: FCC Title 47 Part 15 (15.107 & 15.109)
Safety	EN IEC 62368-1:2020+A11:2020
Immunity	EN 301 489-1 V2.2.3 EN 301 489-17 V3.2.4

Parts included

Quantity	Component
1	Wireless installation dongle
1	USB type-C cable
1	Quick installation guide

Technical specifications

Connectivity

Connectivity technology	Wireless
Host Interface	USB
Interface	WLAN
USB Version	2.0

Network

Wireless technology standard	Wi-Fi
Wi-Fi standard	IEEE 802.11n; IEEE 802.11g; IEEE 802.11b
Operating range	11b: 1/2/5.5/11 Mbps 11g: 6/9/12/24/36/48/54 Mbps 11n (20 MHz): MCS0-07, up to 72 Mbps 11n (40 MHz): MCS0-07, up to 150 Mbps
Security algorithms	WEP 64/128-bit, WPA, WPA2; WPA3; WPS
Antenna type	Internal
Frequency band	2.4 GHz

Mechanical

Dimensions (H x W x D) (mm)	7.1 mm x 14.9 mm x 17.5 mm
Dimensions (H x W x D) (in)	0.28 in x 0.59 in x 0.69 in
Weight (g)	2 g
Weight (lb)	0.004 lb
Color	Black

Environmental

Operating temperature (°C)	0 °C – 40 °C
Operating temperature (°F)	32 °F – 104 °F
Storage temperature (°C)	-20 °C – 60 °C
Storage temperature (°F)	-4 °F – 140 °F
Operating relative humidity, non-condensing (%)	0% – 90%
Storage relative humidity (%)	0% – 95%

Ordering information

NCA-WLAN-EU Wireless installation dongle EU

Wireless installation dongle for wireless commissioning
Order number **NCA-WLAN-EU | F.01U.405.793**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com